



(19)

Generated Document.

(11) Publication number:

63003414 A**PATENT ABSTRACTS OF JAPAN**(21) Application number: **61147380**(51) Intl. Cl.: **H01L 21/205**(22) Application date: **24.06.86**

(30) Priority:

(43) Date of application
publication: **08.01.88**(84) Designated contracting
states:(71) Applicant: **AGENCY OF IND SCIENCE &
TECHNOL****SHIN ETSU CHEM CO LTD
SEIKO INSTR & ELECTRONICS
LTD**(72) Inventor: **HAYASHI YUTAKA****YAMANAKA MITSUYUKI
UMEMURA MITSUO
OKAZAKI SATOSHI
TAKADA RYOJI
KAMIYA MASAOKI**

(74) Representative:

**(54) MANUFACTURE OF
SILICON FILM**

(57) Abstract:

PURPOSE: To form an amorphous
silicon film having a sufficient
deposition rate and excellent electric
characteristics by a method wherein a

thermal CVD method is performed at the substrate temperature of 480°C or below using trisilane or higher silanes.

CONSTITUTION: The substrate 4 consisting of a wafer and the like is inserted into the chamber 1 consisting of a heating means 2, a susceptor 3, a gas blow-out hole 5, the exhaust hole and the like connected to a gas exhaust means 7, they are placed on the upper surface of the susceptor 3. When they are heated up to 400°C or thereabout by a heating means 2, the silane of high order which is higher than trisilane is introduced into the chamber 1. As a result, an amorphous silicon film is formed on the surface of the substrate 4 by thermal decomposition reaction. At this time, atmospheric gas is introduced into the chamber 1 in advance, and after the temperature of the substrate 4 has been stabilized, raw gas is introduced, and the temperature variation when a film is formed can be made small substantially by performing a thermal CVD.

COPYRIGHT: (C)1988, JPO&Japio



